We reserve all rights for the drawing even for case of patent grant or registration of design patent. This drawing may not be regroduced nor made accessible to a third party without our prior agreement. And it may not be improperly made use of in any other way by the receiver or third party. Infringements would necessitate compensation and might lead to criminale procedure.

Für diese Zeichnung behalten wir uns alle Rechte vor, auch für den Fall der Patenterteilung oder Gebrauchsmustereintragung. Ohne unsere vorherige Zustimmung darf diese Zeichnung weder vervielfältigt noch Dritten zugänglich gemacht werden, und sie darf durch den Empfänger oder Dritte auch nicht in anderer Weise mißbräuchlich verwertet werden. Zuwiderhandlungen verpflichten zu Schadenersatz und können strafrechtliche Folgen haben.

081006/rev.5

[0,3594 +0,0035 -0,0031]
∅9,13 +0,090 -0,080
A

[0,3012 +0,0008 -0,0039]
∅7,65 +0,020 -0,100
⌖ ∅ [0,0039] A
⌖ ∅ 0,1 A

[0,2]
∅5,08

A

[0,0118 min.]
0,3 min.

[0,0701]
∅1,78

[0,0354 ±0,0039]
0,9 ±0,100

B

[0,0315 ±0,0039]
0,8 ±0,100

45°

[0,0079 max.]
R0,2 max.

A

[0,0118 max.]
0,3 max.
Glassverlauf
glass meniscus

B (20 : 1)

[0,0118 max.]
0,3 max.
Glassverlauf
glass meniscus

[0,0118 max.]
0,3 max.
Glassverlauf
glass meniscus

A-A

[0,0079 max.]
R0,2 max.

[0,0157 +0,0020 -0,0024]
0,4 +0,050 -0,060

NiFeCo
(1.3981)

hartgelötet
brazed

NiFeCo
(1.3981)

[0,0177 +0,0008 -0,0020]
∅0,45 +0,020 -0,050

⌖	∅	[0,0142]	Ⓜ	C	Ⓜ	A	Ⓜ	B	Ⓜ
⌖	∅	0,36	Ⓜ	C	Ⓜ	A	Ⓜ	B	Ⓜ

C

[0,0354 +0,0028 -0,0020]
∅0,9 +0,070 -0,050

▱	[0,0002/0,0039/ø0,0295]		
▱	0,005/0,1/ø0,75		

//	[0,002/ø0,0295]	C
//	0,05/ø0,75	C

NiFeCo
(1.3981)

Glas
glass

B

▱	[0,002]
▱	0,05

[0,0138 ±0,0039]
0,35 ±0,100

[0,5315 ±0,0197]
13,5 ±0,500

[0,0591 ±0,0039]
1,5 ±0,100

Liefervorschrift/Delivery specification				SPC-Dimension kritische Maße für Prozessfähigkeit / critical dimensions for process capability		Allgemeine Werkstückkanten DIN ISO 13715 / Gen. edges of working part DIN ISO 13715
Oberfläche/Surface:		Gewicht/weight: 0.649 g		Oberflächenrauheit DIN ISO 1302 Surface roughness: Ra 3,2 [125]		
				Einheit/Unit: mm[in]	Proj. Nr.:	Material:
				Freimaßtol./Gen.Tol.: DIN ISO 2768-mK		Maßstab/Scale: 10:1
					Datum/Date / Name	Format/Size: A3
				Drawn	891214 / Reithofer	
				Check.	120710 / LIS	
7-B	B2326	09.07.2012	DEG	GLDF - TRANSISTOR - TO39		D4.211306
7	P1192	060329	LIS	GTMS - TRANSISTOR - TO39		
Index	Änderung/Issue	Datum/Date	Name			Blätter/Pages:2 / Blatt/Page: 2

Gehört für:
used for:

electrovac hermetic packages

Proj. Europ.