



NOTES: 1. GOLD PLATE 60μ INCHES MIN OVER 80μ INCHES MIN. NICKEL.

2. LEAD RESISTANCE

No. 3, 4, 5, 6, 16, 17, 20, 21, 22, 25, 30, 47, 49 ARE 100 mΩ MAX.  
ALL OF OTHER LEADS ARE 300 mΩ MAX.

3. PIN No 25 IS ELECTRICALLY CONNECTED TO THE DIE ATTACH PAD. SEAL RING ISOLATED.

NTK TECHNICAL CERAMICS DIVISION  
APR 27 1985  
NTK SPARK PLUG CO., LTD.

Rev.	Description	Date				
A	RE DRAWING	Apr-1-85				
Φ	NEW DRAWING (DA-6687)	Mar-77-85				
Item	Part No	Material	Description	Rev.	Description	Date
UNLESS OTHERWISE SPECIFIED TOLERANCES: + 1% N. L. T. 2 DECIMALS .XX ± .01 3 DECIMALS .XXX ± .005				DRAWN <i>M. Merita</i>	NTK TECHNICAL CERAMICS NGK SPARK PLUG CO., LTD	
				CHECKED	TITLE 64 LD CHIP CARRIER	
				APPROVED <i>J. Cox</i>	DWG NO. IRK64FI-281A	
				UNIT INCH	SIZE A-3	
				SCALE		