



- NOTES
1. PLATING THICKNESS TO BE PER CUSTOMER'S SPECIFICATION.
 2. CAMBER : .005"/IN. NLT. .004"
 3. SEAL AREA TO BE METALLIZED
 4. DIE ATTACH AREA TO BE NOT METALLIZED.
 5. SEAL RING TO BE FLOATING FROM ANY PINS.

SK=0
HBO16M714-1 D=N

MODIFICATIONS	DELETED: W/B PATTERN MARK	FEB. 19 '88	H. Yamashita	NAME	HYBRID 16 LEAD PACKAGE		TOLERANCES:	DRAWN	CHECKED
	CHANGED: .890 ± .015 → ± .010	SEP. 17 '83	J. Higashigata	SCALE	MATERIAL		UNLESS OTHERWISE SPECIFIED	APPROVED	DATE
	ADDED: VENDOR'S OPTION AT TIE-BAR	APR. 22 '83	A. Yamashita	5 : 1	AS INDICATED		± .005		
	CHANGED: ± .005 ± .003, NOTES, 1	FEB. 10 '83	K. Oishi						OCT. 22 '82
	CHANGE	DATE	DRAWN	CHECKED	APPROVED	KYOCERA CORPORATION KYOTO JAPAN		DWG. NO.	KD-82714-D