


NOTE

1. DUST AND SCRATCH : $20 \mu\text{m}$ MAX(A-ZONE)
(DUST AND CONTAMINATION SHALL BE ACCEPTABLE IF REMOVABLE WITH AIR BLOW AT 294kPa OR STICKY GLUE. AND NOT BEING THE STAIN/DIRT TO GIVE A SPECTRUM CHARACTERISTIC BAD INFLUENCE.)
2. CHIPS
 $X \leq 1.50\text{mm}$
 $Y \leq 0.50\text{mm}$
 $Z \leq 0.275\text{mm}$
3. SPEC : KSD-248-0091 (LATEST Rev.)
4. EPOXY TECHNICAL SHEET : KSD-248-0105 (LATEST Rev.)



MODIFICATIONS									
	-	INITIAL	Dec.21.'09	<i>Murawski</i>	<i>R. Myata</i>	<i>I. Citate</i>	<i>T. Nabeo</i>	<i>S. Tadama</i>	<i>K. Chikatsu</i>
REV	CHANGE	DATE	APPROVED	CHECKED	CHECKED	CHECKED	CHECKED	CHECKED	DRAWN
NAME	13.60SQ x 0.55 GLASS LID		TOLERANCES	SCALE		MATERIAL		1 / 1	
DRAWING NO.	KO-LI0093032		± 0.10	5 : 1		D263Teco			
				UNIT		mm			
CAUTION	THIS DRAWING CONTAINS THE CLASSIFIED INFORMATION ON KYOCERA CORPORATION. INDICATING TO THE THIRD PARTY OR COPYING ALL OR PART OF THE CONTENT IS STRICTLY PROHIBITED WITHOUT WRITTEN PERMISSION FROM KYOCERA CORPORATION.								