


NOTES

1. ALL EXPOSED METALLIZED AREA SHALL BE GOLD PLATED 60 MICRO INCH MIN. THK. OVER NICKEL PLATED UNLESS OTHERWISE SPECIFIED PURCHASE ORDER.
2. FLATNESS METALLIZED PADS ONLY.
3. SEAL AREA AND DIE ATTACH AREA SHALL BE ISOLATED FROM ANY LEADS. (ZERO GROUND)
4. LEAD TO LEAD LEAKAGE MUST NOT EXCEED 5 NANO AMPS AT 100V D.C
5. LEAD RESISTANCE 0.3 Ω MAX.

MODIFICATIONS

| | | | | | |
|--------|--|------|-------|---------|----------|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| CHANGE | | DATE | DRAWN | CHECKED | APPROVED |

NAME 16 LCC (HBO-16C)
 SCALE 10/1
 MATERIAL KYOCERA A-440


TOLERANCES:
 UNLESS OTHERWISE SPECIFIED
 ± 1 %
 N.L.T. ± .005

| | | | |
|--------------------------|---------|----------|------------|
| HBO-16C | | | |
| DRAWN | CHECKED | APPROVED | DATE |
| S.M | UE. K.H | M.S | MAR.16.'99 |
| DRAWING NO. PB-C85194 | | | SHEET / |