


- NOTES
1. ALL EXPOSED METALLIZED AREA SHALL BE GOLD PLATED 60 MICRO INCHES MIN. THK. OVER NICKEL PLATE UNLESS OTHERWISE SPECIFIED IN PURCHASE ORDER.
 2. FLATNESS PERTAINS TO METALLIZED PADS ONLY.
 3. SEAL AREA AND DIE ATTACH AREA SHALL BE ISOLATED FROM ALL LEADS. (ZERO GROUND)
 4. LEAD TO LEAD LEAKAGE SHALL NOT EXCEED 10 NANO AMPS AT 100V D.C
 5. LEAD RESISTANCE : 1.0 Ω MAX..
 6. CAPACITANCE: 3.0pF MAX. 1000Hz.
 7. NO METALLIZATION ON BACK SIDE.
 8. LEAD PULL STRENGTH TO BE 0.5 LBS MIN. PERPENDICULAR PULL.

ALUMINA COAT
KYOCERA A-440

LEAD: Fe-Ni-Co ALLOY
OR ALLOY 42



MODIFICATIONS						NAME	TOLERANCES:		DRAWN	CHECKED	APPROVED	DATE
						132 CQFP (.400 SQ. CAV.)	UNLESS OTHERWISE SPECIFIED		T.I	T.Y	K.L	Y.S
						SCALE 8/1	±.005					186-2-22
	△ ADDED: L/F MATERIAL Fe-Ni-Co ALLOY CHANGE	06.APR.95	H.U	A.Y	U.E	T.D	THIRD ANGLE PROJECTION		DRAWING NO.			SHEET 1/2
							KYOCERA CORPORATION KYOTO JAPAN		PB-F86099-A			

