



- NOTES;
1. ALL EXPOSED METAL AND METALLIZED AREA SHALL BE GOLD PLATED 1.5 μm MIN. THICKNESS OVER NICKEL PLATED.
 2. SEAL AREA AND DIE ATTACH PAD SHALL BE ISOLATED FROM ANY LEADS. (ZERO GROUND)
 3. * INDICATES DIMENSION OF THE TOP SURFACE.

MODIFICATIONS						NAME	TOLERANCES:	PGO-20F			
NO.	DESCRIPTION	DATE	DRAWN	CHECKED	APPROVED	20 LEAD S.O. PACKAGE	UNLESS OTHERWISE SPECIFIED	DRAWN	CHECKED	APPROVED	DATE
1	CHANGED CAV,S/R,THK DIM & B/F EXPOSURE	01.25.'88	Y.S	T.T		SCALE 10/1	± 0.13	K.I	N.U	S.T	11.04.'86
2	CHANGED LEAD FRAME FORMING	03.04.'87	K.A	N.U	S.T	MATERIAL KYOCERA A-440	THIRD ANGLE PROJECTION				
3	CHANGED W/B PATTERN, 12.9 ± 0.18 → 12.80 ± 0.18	01.21.'87	K.A	N.U	Y.S	KYOCERA		DRAWING NO. PB-F86652-C			SHEET 1/1
	CHANGE	DATE	DRAWN	CHECKED	APPROVED	KYOCERA CORPORATION KYOTO JAPAN					