



NOTES:

- ALL EXPOSED METAL AND METALLIZED AREA SHALL BE 60 MICRO INCHES MIN. THK. OVER NICKEL PLATED UNLESS OTHERWISE SPECIFIED PURCHASE ORDER. GOLD PLATED SS
- FLATNESS METALLIZED PADS ONLY.
- SEAL AREA AND DIE ATTACH AREA SHALL BE ISOLATE FROM ANY LEADS. (ZERO GROUND)

|               |  |  |  |                             |  |  |  |            |  |                       |  |                                 |  |                            |  |
|---------------|--|--|--|-----------------------------|--|--|--|------------|--|-----------------------|--|---------------------------------|--|----------------------------|--|
| MODIFICATIONS |  |  |  | NAME 84CQFJ (.300 SQ. CAV.) |  | TOLERANCES: UNLESS OTHERWISE SPECIFIED |  | DRAWN T.I. |  | CHECKED S.M.          |  | APPROVED Y.S.                   |  | DATE 9-10-'92              |  |
| CHANGE        |  |  |  | SCALE 6/1                   |  | MATERIAL KYOCERA A-440                 |  | ± .005     |  | DRAWING NO. PB-F92942 |  | SHEET                           |  |                            |  |
| DATE          |  |  |  | DRAWN                       |  | CHECKED                                |  | APPROVED   |  | KYOCERA               |  | KYOCERA CORPORATION KYOTO JAPAN |  | 31-0307-01-A MOD JNA-84-05 |  |